



1900 Albany Place SE
 P.O. Box 286
 Orange City, IA 51041

800-747-3436 Fax 712-737-3893
 www.oldmastrs.com

PRODUCT INFORMATION

LIQUID PAINT REMOVER - TM-1

PRODUCT NO.	00101, 00104, 00105, 00150
GENERIC TYPE	Paint stripper, liquid, solvent type
COLOR	Light blue
GLOSS	Not applicable
SOLIDS BY WEIGHT	1.0%
SOLIDS BY VOLUME	1.0%
THEORETICAL COVERAGE @ 1 MIL DFT	Not applicable
COVERAGE @ RECOMMENDED DFT	Not applicable
RECOMMENDED DFT PER COAT	Not applicable
WEIGHT PER GALLON	7.64 lbs.
FLASH POINT	19°F Tag Closed Cup
USE	Removes paint, enamel, lacquer, shellac, and polyurethane from wood, metal, and masonry.
VISCOSITY AT 77°F	14 sec. #2 Zahn Cup
AVERAGE DRY TIME AT 70°F & 50% R.H.	Not applicable.
RECOMMENDED THINNER	Methylene chloride
APPLICATION	Apply a liberal coat with a bristle brush.
SURFACE PREPARATION	None required. Remove finish with a scraper, steel wool, or burlap cloth.
CLEAN UP	Toluene

FOR THE LOVE OF WOOD®

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



PRODUCT INFORMATION

LIQUID PAINT REMOVER - TM-1

OLD MASTERS® TM-1, a fast-acting liquid remover, is specially formulated to remove old finishes from furniture and antiques. TM-1 strips varnish, paint, enamel, lacquer and shellac from wood, metal or masonry without harming the original surface. TM-1 is ideal for both dipping and brush applications and is also excellent for removing old finishes from flat or horizontal surfaces. TM-1 is economical and practical as a commercial soak remover. For vertical or heavy coated surfaces, we recommend the OLD MASTERS® TM-4® heavy-bodied paint remover. TM-1 is flammable, and as with all removers, we recommend use of gloves, ample ventilation, and normal caution when working near fire hazards, sparks, electrical receptacles or heat sources.

DIRECTIONS FOR USE

BEFORE YOU BEGIN: Read cautions on side panel carefully. SHAKE WELL before using. Use caution when opening can—remover may build up pressure through temperature changes. Hold rag over cap until pressure is released. Protect sensitive hands with plastic (polyethylene or neoprene) gloves. Use old, inexpensive, or throw-away bristle brush for application. For best results, use when temperature is between 60°F and 85°F, and apply away from strong breezes and hot sun. Do not use on linoleum, rubber, asphalt, or other synthetics.

TO APPLY: Apply a liberal coat of TM-1 to project surface with a bristle brush, brushing in one direction only. Do not brush out as you would paint—this would destroy evaporation retardant. TM-1 is also ideal for dipping small objects. Allow TM-1 time to soften the finish—approximately 30 minutes, depending on the number of coats of old finish. Old finish is ready for removal when it blisters, wrinkles, or can be lifted off easily with a flat scraper.

TO REMOVE: Use a round-cornered scraper, steel wool, and/or burlap cloth to remove old finish. Test scrape in a small area to be sure finish is ready for removal. If old finish removes easily, continue scraping project gently in the direction of the wood grain. Be careful to avoid gouging. If finish is particularly stubborn, remove loose residue by scraping, then repeat application. A toothbrush, fine wire brush, or a pointed stick will help remove finish buried in carving and recesses. To complete cleaning, use fine steel wool dipped in TM-1 and wipe with the grain. Wipe surface with clean cloth, and let dry. TM-1 contains no acids or alkali—neutralizing is not required.

TO REFINISH: Allow the surface to dry thoroughly. Sand lightly in the direction of the wood grain before applying the new finish.

CAUTION:

**CONTAINS METHANOL, METHYLENE CHLORIDE, ACETONE, AND TOLUOL.
CANNOT BE MADE NON-POISONOUS.**

Do not use or store near heat, sparks, electrical receptacles, fire or flame. Avoid breathing vapor or contact with skin or eyes. **FIRST AID:** If swallowed, immediately give 1 or 2 glasses of water and call a Physician, Hospital Emergency Room or Poison Control Center for way to induce vomiting. In case of eye contact, immediately flush thoroughly with water and call a Physician. For skin contact, wash thoroughly. Open container carefully and close after each use. Do not transfer contents to unlabeled bottles or other containers. **Use only with adequate ventilation.** Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Chronic exposure may cause damage to the central nervous system, respiratory system, lung, eye, skin, liver, gastrointestinal tract, spleen, kidneys and blood.

KEEP OUT OF REACH OF CHILDREN.

Limited Warranty

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

OLD MASTERS®
1900 ALBANY PLACE SE
ORANGE CITY, IA 51041