



1900 Albany Place SE  
P.O. Box 286  
Orange City, IA 51041

800-747-3436 Fax 712-737-3893  
www.oldmastrs.com

## PRODUCT INFORMATION

### ***FURNITURE REFINISHER***

<b>PRODUCT NO.</b>	00601, 00604, 00608
<b>GENERIC TYPE</b>	Solvent Finish Remover
<b>COLOR</b>	Clear
<b>GLOSS</b>	Not applicable
<b>SOLIDS BY WEIGHT</b>	None
<b>SOLIDS BY VOLUME</b>	None
<b>THEORETICAL COVERAGE @ 1 MIL DFT</b>	Not applicable
<b>COVERAGE @ RECOMMENDED DFT</b>	Not applicable
<b>RECOMMENDED DFT PER COAT</b>	Not applicable
<b>WEIGHT PER GALLON</b>	7.60 lbs.
<b>FLASH POINT</b>	14°F Tag Closed Cup
<b>USE</b>	Removes varnish, lacquers and shellac.
<b>VISCOSITY AT 77°F</b>	14 sec. #2 Zahn Cup
<b>AVERAGE DRY TIME AT 70°F &amp; 50% R.H.</b>	Not applicable
<b>RECOMMENDED THINNER</b>	Thinning is not recommended. Use as it comes from the can.
<b>APPLICATION</b>	Apply with #0000 steel wool.
<b>SURFACE PREPARATION</b>	None required
<b>CLEAN UP</b>	Go over entire surface with clean refinisher, buff down with a clean towel and allow to dry.

**FOR THE LOVE OF WOOD®**

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



# PRODUCT INFORMATION

## **OLD MASTERS® FURNITURE REFINISHER**

OLD MASTERS® FURNITURE REFINISHER, a fast-acting liquid remover, is excellent for dissolving varnish, lacquer or shellac. OLD MASTERS® REFINISHER will not destroy the patina or natural color of wood. It will not raise the grain or loosen glue joints, veneers, inlays, wood fillers or laminated woods. It is also an effective remover wash following paint removal. REFINISHER is flammable: use gloves, safety glasses, ample ventilation, and exercise normal caution when working near fire hazards, sparks, electrical receptacles or heat sources.

**DIRECTIONS FOR USE:** Read the entire label, its directions and cautions. Open with caution. Hold rag over cap until pressure is released.

For best results, use when temperature is between 60°F and 85°F and apply away from strong breezes and hot sun.

Pour a small amount of OLD MASTERS® REFINISHER into a wide mouth jar. Dip a small piece of steel wool in the REFINISHER. Squeeze out excess.

Gently rub the surface with the dampened steel wool. Work within a small area. As the old finish becomes tacky, rinse and squeeze the steel wool in the work jar. Continue until all tackiness and residue is removed from the working area.

Repeat on adjacent areas, overlapping each work area until the entire piece is clean. Rub surface with long strokes following woodgrain—use clean refinisher and steel wool. Buff with clean, dry steel wool or towel. Allow surface to dry thoroughly. Apply finish coat when surface is completely dry and dust free. We recommend OLD MASTERS® TUNG OIL finishes for a hand rubbed finish, or OLD MASTERS® varnishes for a protective finish.

## **CAUTION!**

**CONTAINS METHYLENE CHLORIDE, METHANOL, TOLUENE AND ACETONE.  
CANNOT BE MADE NON-POISONOUS.**

Avoid prolonged and repeated breathing of vapors or contact with skin or eyes. In case of contact with eyes, immediately flush thoroughly with water and get medical attention. For skin contact, wash thoroughly. If swallowed, give one or two glasses of water. Call physician, hospital emergency room or Poison Control Center immediately for instructions to induce vomiting. When medical advice is not available, induce vomiting using syrup of ipecac according to directions. If ipecac is unavailable, induce vomiting with finger or the back of a spoon. Get prompt medical attention. Contact with flame or hot surfaces may produce toxic gases. Open container carefully and close after each use. Do not transfer contents to unlabeled bottles or other containers.

As with other methylene chloride solvent based paint strippers, the following cautions would apply: Contains methylene chloride, which has been shown to cause cancer in certain laboratory animals. Risk to your health depends on level and duration of exposure. Use this product outdoors, if possible. If you must use it indoors, open all windows and doors or use other means to ensure fresh air movement during application and drying. If properly used, a respirator may offer additional protection. Obtain professional advice before using. A dust mask does not provide protection against vapors. Do not use in basement or other unventilated area. Open container carefully and close after each use. Clean up rags, papers, and waste promptly. Allow solvent to evaporate, then dispose of in metal containers.

Reports have associated repeated and prolonged occupational over-exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Chronic exposure may cause damage to the central nervous system, respiratory system, lung, eyes, skin, liver, gastrointestinal tract, spleen, kidneys and blood.

KEEP AWAY FROM HEAT, SPARKS AND FLAME. USE ONLY IN WELL-VENTILATED AREAS.

**KEEP OUT OF REACH OF CHILDREN.**

---

### **Limited Warranty**

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

---

OLD MASTERS®  
1900 ALBANY PLACE SE  
ORANGE CITY, IA 51041