



1900 Albany Place SE
P.O. Box 286
Orange City, IA 51041

800-747-3436 Fax 712-737-3893
www.oldmastrs.com

PRODUCT INFORMATION

NON-METH PAINT REMOVER - TM-2

PRODUCT NO.	00701, 00704, 00705, 00750
GENERIC TYPE	Paint stripper, creamy-bodied solvent type
COLOR	Not applicable
GLOSS	Not applicable
SOLIDS BY WEIGHT	5.0%
SOLIDS BY VOLUME	3.5%
THEORETICAL COVERAGE @ 1 MIL DFT	Not applicable
COVERAGE @ RECOMMENDED DFT	Not applicable
RECOMMENDED DFT PER COAT	Not applicable
WEIGHT PER GALLON	6.70 lbs.
FLASH POINT	41°F Tag Closed Cup
USE	Removes paint, enamel, lacquer, shellac, and polyurethane from wood, metal, and masonry.
VISCOSITY AT 77°F	2100 cps using Brookfield viscometer
AVERAGE DRY TIME AT 70°F & 50% R.H.	Not applicable. Apply a heavy enough coat to prevent surface drying out before removal of surface coating.
RECOMMENDED THINNER	Toluene
APPLICATION	Apply a heavy coat with a natural bristle brush.
SURFACE PREPARATION	None required. Remove finish with a scraper, steel wool, or burlap cloth.
CLEAN UP	Water wash

FOR THE LOVE OF WOOD®

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



PRODUCT INFORMATION

NON-METH PAINT REMOVER - TM-2

OLD MASTERS® TM-2 is a non-methylene chloride, creamy-bodied paint remover in the quality water wash class. It completely removes paint, enamel, varnish, lacquer, shellac and polyurethane from wood, metal and masonry. Its creamy-bodied consistency lets it cling to vertical surfaces, as well as making it convenient to spread on horizontal surfaces. A long wet edge makes TM-2 ideal for big jobs. TM-2's water wash formula makes it easy to use—wash off or scrape off multiple coats in one operation. It contains no acids. It needs no neutralizing or after wash. TM-2 is flammable, and as with all removers, we recommend the use of gloves, ample ventilation, and normal caution when working near fire hazards, sparks, electrical receptacles or heat sources.

DIRECTIONS FOR USE

BEFORE YOU BEGIN: Read cautions on side panel carefully. SHAKE WELL before using. Use caution when opening—remover may build up pressure through temperature changes. Hold rag over cap when opening until pressure is released. Use old, inexpensive, or throw-away bristle brush for application. Protect sensitive hands with plastic (polyethylene or neoprene) gloves. For best results, use when temperature is between 60°F and 85°F, and apply away from strong breezes and hot sun. Clean up used rags, paper, and waste promptly. (Take outdoors. Allow liquid to evaporate and sludge to dry, then dispose of in a metal container.)

TO APPLY: Apply a liberal coat of OLD MASTERS® TM-2, brushing in one direction only. Do not brush out as you would paint—this would

destroy evaporation retardant. Allow TM-2 time to soften the finish—approximately 15 to 30 minutes, depending on the number of coats of old finish. Thick layers may require more time. Old finish is ready for removal when it blisters, wrinkles, or can be lifted off easily with a flat scraper.

TO REMOVE: Scrape-Off Method: Use a round-cornered scraper, steel wool, and/or burlap cloth to remove old finish. Test scrape in a small area to be sure finish is ready for removal. If old finish removes easily, continue scraping project gently in the direction of the woodgrain. Be careful to avoid gouging. Repeat application if finish is particularly stubborn. To remove stubborn spots, rub lightly with fine steel wool that has been dipped in TM-2. A toothbrush, fine wire brush, or a pointed stick will help remove finish buried in carving and recesses. To complete cleaning, use fine steel wool dipped in TM-2 and wipe with the grain. Wipe surface with clean cloth, and let dry. Neutralizing is not required. Water Wash-Off Method: Rub prepared surface with wet toweling, burlap, or fine steel wool and water to form a creamy emulsion. Use a wet toothbrush to get into carvings or grooves. Rinse off emulsion with wet cloth or sponge. Flush with water from a hose when possible and wipe dry. Plywood and veneers should be dried promptly.

TO REFINISH: After either method of removal, be sure all dissolved residue is removed and the surface is completely clean and dry. Sand lightly in the direction of the woodgrain before applying the new finish.

CAUTION:

CONTAINS METHANOL, TOLUOL, AND ACETONE.
CANNOT BE MADE NON-POISONOUS.

Do not use or store near heat, sparks, electrical receptacles, fire or flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin or eyes. **FIRST AID:** If swallowed, immediately give 1 or 2 glasses of water and call a physician, hospital emergency room or poison control center for a way to induce vomiting. In case of eye contact, immediately flush thoroughly with water and call a physician; for skin contact, wash thoroughly. **USE ONLY WITH ADEQUATE VENTILATION.** Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Chronic exposure may cause damage to the central nervous system, respiratory system, lung, eye, skin, liver, gastrointestinal tract, spleen, kidneys and blood.

KEEP OUT OF REACH OF CHILDREN.

Limited Warranty

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

OLD MASTERS®
1900 ALBANY PLACE SE
ORANGE CITY, IA 51041