

1900 Albany Place SE  
P.O. Box 286  
Orange City, IA 51041

800-737-3436 Fax 712-737-3893  
www.oldmastrs.com


## PRODUCT INFORMATION

### **QUICK DRY VARNISH — SEMI-GLOSS**

<b>PRODUCT NO.</b>	49801, 49804, 49805
<b>COLOR</b>	Clear
<b>GLOSS</b>	55 to 65 @ 60°
<b>SOLIDS BY WEIGHT</b>	37%
<b>SOLIDS BY VOLUME</b>	28 to 29%
<b>V.O.C.</b>	543 grams/liter
<b>THEORETICAL COVERAGE @ 1 MIL DFT</b>	450 sq. ft. per gal.
<b>COVERAGE @ RECOMMENDED DFT</b>	300 to 450 sq. ft. per gal.
<b>RECOMMENDED DFT PER COAT</b>	1 to 1½ Mils
<b>WEIGHT PER GALLON</b>	7.1 to 7.2 lbs.
<b>FLASH POINT</b>	44°F
<b>USE</b>	Use on all interior bare or previously finished wood surfaces.
<b>VISCOSITY AT 77°F</b>	60 to 62 KU
<b>AVERAGE DRY TIME AT 70°F &amp; 50% R.H.</b>	Dry to touch in 30 minutes. Tack free in 1 to 2 hours. Recoat after 3 hours.
<b>RECOMMENDED THINNER</b>	Do not thin.
<b>APPLICATION</b>	Apply by brush, pad, roller, or sprayer. Flow on generously in the direction of the grain with minimal brush strokes.
<b>SURFACE PREPARATION</b>	Surface must be clean, dry, and free from dirt, dust, wax, and grease. Sand bare wood smooth and remove dust. Sand previously finished wood to remove imperfections and gloss. Remove dust with tack rag.
<b>CLEAN UP</b>	Mineral Spirits

**FOR THE LOVE OF WOOD®**

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



# PRODUCT INFORMATION

## QUICK DRY VARNISH — SEMI-GLOSS

**DESCRIPTION:** OLD MASTERS® QUICK DRY VARNISH is a high quality alkyd varnish combining high build with beauty and endurance. Its fast drying, self-sealing formulation allows same day multiple coat application. The tough clear finish is resistant to abrasion, alcohol and most household chemicals, and will retain a beautiful gloss for years. It is compatible with most finishes and may be used on new or previously finished interior wood surfaces such as furniture, doors, trim and cabinets. Non-toxic when dry.

**THINNING:** Do not thin. Use as packaged.

**SURFACE PREPARATION:** The wood surface must be clean, dry, and free from dirt, dust, wax, and grease. Surfaces must be properly prepared prior to application of this product.

**Bare Wood Surfaces:** Eliminate imperfections by sanding the wood thoroughly; begin with a medium grit sandpaper progressing to a fine grit. Always sand in the direction of the woodgrain. Remove dust particles with a tack rag. If stain is to be applied, apply prior to using QUICK DRY VARNISH and allow stain to dry thoroughly.

**Previously Finished Wood:** Sand with a fine grit sandpaper to remove surface imperfections and gloss. Remove sanding dust with a tack rag, then finish as bare wood surfaces. Wax and/or polish are best removed by wiping thoroughly with mineral spirits. Change rags often and wash until all wax and/or polish is removed.

**APPLICATION INSTRUCTIONS:** Stir well before and during use. For projects requiring more than one container, intermix to ensure gloss uniformity. Equipment must be clean prior to start. Flush sprayer lines with mineral spirits. Apply by brush, pad, roller, or sprayer. A good quality natural bristle brush will make application easier. When coating large surface areas, the use of a 1/4" short nap roller or lambskin pad type applicator are recommended. For airless spraying, use tip sizes .013 to .015. Flow on generously with minimum strokes in the direction of the grain. Two (2) coats are recommended for best results. For high traffic and abrasive conditions, three (3) coats or more are recommended. Allow product to dry before recoating; sand lightly between coats and remove sanding dust with a tack rag. Allow finish to cure for at least 24 hours before subjecting to normal use. Allow finish to fully cure (approximately 72 hours) before using wax or cleaners.

**SPREADING RATE:** May vary depending on surface porosity, application method, and material loss during application.

Recommended DFT per coat..... 1 to 1.5 mils  
Spread rates @ Rec. DFT..... 300 to 400 ft<sup>2</sup>/gal

**DRYING TIME:** QUICK DRY VARNISH will dry to touch in 30 minutes, depending on temperature and humidity. Recoat after three hours.

**CLEAN UP:** Clean up with mineral spirits.

VOC: 557 grams/liter (4.64 lbs/gal)

## WARNING!

### FLAMMABLE LIQUID AND VAPOR.

Contains: VM&P Naphtha and Mineral Spirits. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES NOSE, THROAT, EYE, AND SKIN IRRITATION. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat, sparks, and flame. VAPORS MAY CAUSE FLASH FIRE. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

**Use only with adequate ventilation.** Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN. First Aid:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

### Limited Warranty

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

OLD MASTERS®  
1900 ALBANY PLACE SE  
ORANGE CITY, IA 51041