



1900 Albany Place SE
P.O. Box 286
Orange City, IA 51041

800-747-3436 Fax 712-737-3893
www.oldmastrs.com

PRODUCT INFORMATION

TUNG OIL VARNISH

PRODUCT NO.	50501, 50504, 50508
GENERIC TYPE	Tung Oil Varnish
COLOR	Clear
GLOSS	90 @ 60° on a non-porous surface
SOLIDS BY WEIGHT	47-48%
SOLIDS BY VOLUME	42-43%
V.O.C.	450 grams/liter
THEORETICAL COVERAGE @ 1 MIL DFT.	678 sq. ft.
COVERAGE @ RECOMMENDED DFT.	Not applicable
RECOMMENDED DFT. PER COAT	.5 - 1.0 mil
WEIGHT PER GALLON	7.1 - 7.2 lbs.
FLASH POINT	102 degrees F.
USE	Tung oil and varnish blended to protect and enhance wood surfaces.
VISCOSITY AT 77° F.	25-30S #2 Ford
AVERAGE DRY TIME AT 70°F. & 50% R.H.	4-6 hours
RECOMMENDED THINNER	Do not thin.
APPLICATION	Apply with lint-free cloth or brush on and wipe off excess with a cloth.
SURFACE PREPARATION	Must be clean, well sanded and free from dust.
CLEAN-UP	Mineral spirits. To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed metal container.

FOR THE LOVE OF WOOD®

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



PRODUCT INFORMATION

OLD MASTERS® TUNG OIL VARNISH

For a beautiful hand-rubbed effect on previously stained or bare wood, use OLD MASTERS® TUNG OIL VARNISH. TUNG OIL VARNISH, a superior quality finish made from a blend of tung oil and fine varnishes, dries to a durable, non-oily finish that is water and alcohol resistant. It penetrates the wood surface to protect fine furniture, enhancing the natural beauty and richness of the wood grain.

DIRECTIONS FOR USE: Surface to be finished must be clean, dry and dust free. Apply OLD MASTERS® TUNG OIL VARNISH with a lint-free cloth, rubbing in the direction of the woodgrain. May

also use brushing application, brushing in the direction of woodgrain and wiping off excess with a clean lint-free cloth. Allow the surface to dry 4-6 hours. Buff lightly with fine steel wool and remove dust prior to recoating. Subsequent coats of TUNG OIL VARNISH will increase the depth and luster of the finish.

Do not thin. Use as packaged.

For clean up, use mineral spirits. Promptly discard soiled rags in a water-filled container to prevent spontaneous combustion.

MAX. VOC: 450 grams/liter (3.75 lbs/gal)

DANGER!

HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE LIQUID AND VAPOR.

CONTAINS PETROLEUM DISTILLATE. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES NOSE, THROAT, EYE, AND SKIN IRRITATION. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat and flame. **Use only with adequate ventilation.** Close container after each use. Avoid prolonged contact with eyes, skin, clothing, and vapors. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN.**

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. If swallowed, do not induce vomiting. Call physician immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

Limited Warranty

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

OLD MASTERS®
1900 ALBANY PLACE SE
ORANGE CITY, IA 51041