



1900 Albany Place SE
P.O. Box 286
Orange City, IA 51041

800-737-3436 Fax 712-737-3893
www.oldmastrs.com

PRODUCT INFORMATION

PERFECT MATCH® PENETRATING STAIN TINT BASE

PRODUCT NO.	52001, 52004
GENERIC TYPE	Neutral Base Tint Base (Penetrating Stain Formula)
COLOR	Clear
GLOSS	N/A
SOLIDS BY WEIGHT	33-34%
SOLIDS BY VOLUME	29-30%
VOC	550 grams/liter
SPREADING RATE	300-500 sq. ft. per gal.
WEIGHT PER GALLON	6.9-7.0 lbs.
FLASH POINT	102° F.
USE	A tint base formulated for the creation of custom wood stain colors using universal colorants.
VISCOSITY AT 77° F.	25 Sec #2 Ford Cup
AVERAGE DRY TIME AT 70°F. & 50% R.H.	4 hours
RECOMMENDED THINNER	Do not thin.
APPLICATION	Apply with brush, lint-free cloth, or sprayer. Allow the stain to penetrate 2 to 5 minutes. Before the stain dries, wipe off excess stain with a soft cloth, wiping first across the grain, then with the grain.
SURFACE PREPARATION	The wood surface must be sound, dry, and free from dust, dirt, wax or grease. Sand the wood thoroughly, first with a medium grit sandpaper, then progressing to a fine grit paper. Always sand in the direction of the wood grain. Sand smooth, then remove dust particles with a lint-free rag or a tack rag.
MIXING INSTRUCTIONS	CUSTOM TINTING: Up to 10 ounces of universal colorant may be added per gallon. The product is short-filled in the can to allow room for the appropriate amount of colorant. The amount of colorant added may affect its performance and extend the dry time.
CLEAN-UP	Mineral spirits

FOR THE LOVE OF WOOD®

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



PRODUCT INFORMATION

PERFECT MATCH® PENETRATING STAIN TINT BASE

DESCRIPTION: OLD MASTERS® PERFECT MATCH® PENETRATING STAIN TINT BASE is exclusively formulated for the creation of custom colors using universal colorants. This allows the user to receive all the benefits of unlimited color choice with the outstanding performance of PENETRATING STAIN's fast drying formulation. PENETRATING STAIN is designed for interior wood surfaces, such as cabinets, woodwork, paneling, trim, doors, furniture, floors, etc. It enhances the natural beauty of new interior bare wood surfaces without raising the grain of fine woods.

CUSTOM TINTING: Up to 10 ounces of universal colorant may be added per gallon. The product is short-filled in the can to allow room for the appropriate amount of colorant. The amount of colorant added may affect its performance and extend the dry time.

THINNING: Do not thin. Use as packaged.

SURFACE PREPARATION: The secret to successful application is a properly prepared surface. The wood surface must be sound, dry, and free from dust, dirt, wax, or grease. Sand the wood thoroughly, first with a medium grit sandpaper, then progressing to a fine grit paper. Always sand in the direction of the wood grain. Sand smooth, then remove dust particles with a lint-free rag or a tack rag.

If staining previously finished surfaces, first restore the surface to bare wood by completely removing the old finish, then follow the surface preparation directions listed above.

FILLING: For a smooth topcoat on open grain woods such as oak, mahogany, walnut, ash, etc., you may stain and fill in one application by adding 1 part PENETRATING STAIN to 2 parts Old Masters® WOODGRAIN FILLER. Apply according to the instructions on the filler label.

APPLICATION: Stir well before and during use. For projects requiring more than one container of the same color, stir well, then intermix to avoid any color difference. Apply in an even coat with a brush, cloth, or sprayer. Allow the stain to penetrate 2 to 5 minutes. Before the stain dries, wipe off excess stain with a soft cloth, wiping first across the grain, then with the grain. Allow stain to dry thoroughly before applying topcoat.

HELPFUL HINTS: Color depth may vary according to wood type and application method used. Before staining, test stain in an inconspicuous area. For a deeper color: allow the surface to dry, then apply a second coat. For a lighter color: before the stain has dried, wipe the surface with a cloth dampened with mineral spirits.

SPREADING RATE: Approximately 500 square feet per gallon depending on the porosity and texture of the wood.

DRYING TIME: Approximately 4 hours, depending on humidity and temperature. Be sure surface is thoroughly dry before topcoating. (Note to Professional: Allow 1 hour dry time at normal room temperature before applying lacquer.)

CLEAN UP: Use mineral spirits or paint thinner. Take precautions: oily rags should be promptly discarded into a water-filled container to reduce the risk of spontaneous combustion.

RECOMMENDED FINISH COAT: For added protection, top coat with any Old Masters® Clear Finish.

MAX. VOC: 550 grams/liter (4.6 lbs./gal.)

CONTAINS PETROLEUM DISTILLATE.

VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA. CAUSES NOSE, THROAT, EYE, AND SKIN IRRITATION. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat and flame. **Use only with adequate ventilation.** Close container after each use. Avoid prolonged contact with eyes, skin, clothing, and vapors. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN.** FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. If swallowed, do not induce vomiting. Call physician immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

Limited Warranty

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

OLD MASTERS®
1900 ALBANY PLACE SE
ORANGE CITY, IA 51041