



1900 Albany Place SE
P.O. Box 286
Orange City, IA 51041

800-747-3436 Fax 712-737-3893
www.oldmastrs.com

PRODUCT INFORMATION

H₂O[®] WOOD STAIN

PRODUCT NO.	761 - 766
GENERIC TYPE	Water-based Wood Stain
COLORS	5 pre-mixed colors plus a tint base
GLOSS	Not applicable
SOLIDS BY WEIGHT	9.6% to 15.3%
SOLIDS BY VOLUME	8.4% to 11.2%
V.O.C.	350 grams/liter
THEORETICAL COVERAGE @ 1 MIL DFT	Not applicable
COVERAGE @ RECOMMENDED DFT	Not applicable
RECOMMENDED DFT PER COAT	Not applicable
WEIGHT PER GALLON	8.4 to 8.8 lbs.
FLASH POINT	None
USE	For interior use on bare wood as a penetrating semi-transparent stain
VISCOSITY AT 77°F	58 to 60 KU
AVERAGE DRY TIME AT 70°F & 50% R.H.	Dries in less than 30 minutes. Topcoat after 2 to 3 hours.
RECOMMENDED THINNER	Water
APPLICATION	Apply with brush, lint-free cloth, pad applicator or sprayer. See label for specific surface applications.
SURFACE PREPARATION	The surface must be free from dirt, wax and grease. Wood surfaces should be sanded smooth.
CLEAN-UP	Soap and water

FOR THE LOVE OF WOOD[®]

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



PRODUCT INFORMATION

H₂O® WOOD STAIN

The OLD MASTERS® H₂O® Stain and Clear Program is a new step to professional quality finished projects featuring all of the benefits of a water-based system. H₂O® WOOD STAIN is a water-based semi-transparent stain that colors and enhances the beauty of interior bare wood surfaces. It is ideal for use on cabinets, furniture, doors, trim, crafts, floors, etc. Old Masters®' advanced technology offers a superior product that provides easy application, fast dry, low odor and easy clean-up with soap and water. It comes in factory mixed colors and a tint base that can be custom tinted with universal colorants allowing unlimited color possibilities. H₂O® WOOD STAIN is non-toxic and child-safe when dry.

TINTING SPECIAL COLORS: All Old Masters® stain colors or any custom colors can be created by adding universal colorants to the H₂O® Tint Base. Colortrend formulas for the nine non-premixed Old Masters® stain colors are available upon request.

THINNING: Thinning is not recommended; however a small amount of water may be added to provide a longer wet edge during application.

SURFACE PREPARATION: The wood surface must be clean, dry and free from dirt, wax or grease. Sand the wood thoroughly, first with a medium grit sandpaper, then progressing to a fine grit paper. Always sand in the direction of the woodgrain. Sand smooth, then remove dust particles with a clean cloth. Surface is now ready to stain. If surface is previously finished, restore to bare wood by completely removing the old finish, then follow the surface preparation listed above.

APPLICATION INSTRUCTIONS: Stir well before and during use. Apply a liberal even coat of stain with a nylon/polyester brush, foam brush, staining pad or cloth or sprayer. Maintain a wet edge. While still wet, remove excess with a clean cloth, wiping in the direction of the woodgrain. To avoid lap marks, stain to the end of an area. Never stop in the middle of a surface area. If color penetration is uneven, re-wet the surface with more stain and wipe excess with a clean cloth, blending the uneven areas. If stain dries too fast, reduce stain approximately 5% to 10% with water. Large areas, such as floors, may require two people. Complete small sections with one person applying the stain and the other person wiping the stain. For added color depth, apply additional coats of stain after the first coat has dried thoroughly.

SPREADING RATE: Coverage is approximately 400 square feet per gallon. Spreading rate will vary significantly depending on application method and porosity and texture of wood.

DRYING TIME: Allow stain to dry 2 to 3 hours before applying protective finish. Apply when air and surface temperatures are between 60° and 90°F and humidity is between 30% and 70%. Do not apply below 55°F. Keep from freezing.

CLEAN-UP: Application tools and hands can be cleaned with soap and water.

RECOMMENDED FINISH COAT: We recommend Old Masters® H₂O® Acrylic Varnish or H₂O® Acrylic Polyurethane or any other Old Masters® Clear Finish. Most lacquers, varnishes and polyurethane may be used; however testing for compatibility is recommended.

MAX. VOC: 350 grams/liter (2.92 lbs/gal)

CAUTION!

Do not take internally. Close container after each use. Protect from freezing.
KEEP OUT OF REACH OF CHILDREN.

Limited Warranty

Since Old Masters® does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters® liability will under no circumstances exceed replacement of the product.

OLD MASTERS®
1900 ALBANY PLACE SE
ORANGE CITY, IA 51041